



# STRIPS PRODUCT GUIDE



**FS**  
FieldSELECT™



**75**  
Narrow



**75R**  
Narrow – Round Lens



**75S**  
Narrow – Square Lens



**75W**  
Narrow – Wide Lens



**75L**  
Narrow – Flat Lens



**76**  
Standard



**76R**  
Standard – Round Lens



**GA**  
Aisle Lighter

Click for  
more info →

	FS FieldSELECT™	75 Narrow	75R Narrow – Round Lens	75S Narrow – Square Lens	75W Narrow – Wide Lens	75L Narrow – Flat Lens	76 Standard	76R Standard – Round Lens	GA Aisle Lighter
<b>LUMEN OUTPUT</b>	3,400 to 12,200	1,500 to 24,000	1,500 to 20,000	1,500 to 20,000	1,500 to 20,000	1,000 to 16,000	3,200 to 23,000	3,000 to 18,800	3,500 to 18,000
<b>MAX EFFICACY</b>	152 lm/W	192 lm/W	182 lm/W	182 lm/W	182 lm/W	154 lm/W	200 lm/W	154 lm/W	186 lm/W
<b>LENGTH</b>	4'   8'	2'   3'   4'   8'	2'   3'   4'   8'	2'   3'   4'   8'	2'   3'   4'   8'	2'   4'   8'	4'   8'	4'   8'	4'   8'
<b>MAX AMBIENT TEMP</b>	35°C	50°C	50°C	50°C	50°C	25°C	50°C	50°C	40°C
<b>LISTINGS</b>									
<b>BAA</b>	✓	✓	✓	✓	✓	✓	✓	✓	✓
<b>BABA</b>	✓	✓	✓	✓	✓	✓	✓	✓	✓
<b>QUICKSHIP</b>	✓		✓	✓					
<b>UL 924</b>		✓	✓	✓	✓	✓	✓	✓	✓
<b>DLC QUALIFIED</b>	✓			✓				✓	
<b>MOUNTING</b>									
<b>CONTINUOUS ROWS</b>		✓	✓	✓	✓	✓	✓	✓	✓
<b>AIRCRAFT CABLES</b>		✓	✓	✓	✓	✓	✓	✓	
<b>Y-HANGERS</b>	✓	✓	✓	✓	✓	✓	✓	✓	✓
<b>T-BAR CLIP</b>							✓	✓	✓
<b>STEM &amp; CANOPY</b>							✓	✓	✓
<b>SURFACE MOUNT</b>	✓	✓	✓	✓	✓	✓	✓	✓	✓
<b>45° BRACKET</b>		✓	✓	✓	✓	✓			
<b>OPTIONS</b>									
<b>TUNABLE WHITE</b>		✓	✓	✓	✓	✓			
<b>FIELDSELECT</b>	✓								
<b>EMERGENCY</b>	✓	✓	✓	✓	✓	✓	✓	✓	✓
<b>OCCUPANCY SENSOR</b>		✓	✓	✓	✓	✓	✓	✓	✓
<b>IN-FIXTURE CONTROLS</b>		✓	✓	✓	✓	✓	✓	✓	✓
<b>10KV PROTECTION</b>		✓	✓	✓	✓	✓			✓
<b>WIREGUARD</b>		✓	✓	✓	✓	✓	✓	✓	